



## AVAUNT® 150 EC

Version 4.0 (replaces: Version 3.0)  
Revision Date 11.06.2015

Ref. 130000027381

This Safety Data Sheet adheres to the standards and regulatory requirements of the European Community and may not meet the regulatory requirements of other countries.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : AVAUNT® 150 EC  
Synonyms : DPX-KN128 150EC  
B12109700

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Insecticide

#### 1.3. Details of the supplier of the safety data sheet

Company : DuPont International Operations S.a.r.l.  
2, chemin du Pavillon  
CH-1218 Le Grand-Saconnex / GE  
Switzerland  
Telephone : 41 (0) 22 717 51 11  
Telefax : +41 (0) 22 717 51 09  
E-mail address : sds-support@che.dupont.com

#### 1.4. Emergency telephone number

Emergency telephone number : +(44)-870-8200418  
: Poison Centres may only possess information required for products in  
accordance with Regulation (EC) No 1272/2008 and national legislation.  
Supplier : Du Pont de Nemours (France) S.A.S.  
82, rue de Wittelsheim  
F-68701 Cernay Cedex  
Telephone : +33 (0) 3 89 38 38 38

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to EU Directives 67/548/EEC or 1999/45/EC

Harmful	R22: Harmful if swallowed.
Irritant	R38: Irritating to skin.
Harmful	R48/22: Harmful: danger of serious damage to health by prolonged exposure if swallowed.
Dangerous for the environment	R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.



**AVAUNT® 150 EC**

Version 4.0 (replaces: Version 3.0)  
Revision Date 11.06.2015

Ref. 130000027381

**2.2. Label elements**

Special labelling of certain substances and mixtures      Contains: Indoxacarb / EUH208: May produce an allergic reaction.,

**Labelling according to EU Directives 67/548/EEC or 1999/45/EC**



Harmful



Dangerous for the environment

- R22      Harmful if swallowed.
- R38      Irritating to skin.
- R48/22      Harmful: danger of serious damage to health by prolonged exposure if swallowed.
- R51/53      Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Special labelling of certain substances and mixtures      To avoid risks to man and the environment, comply with the instructions for use.

- S 2      Keep out of the reach of children.
- S13      Keep away from food, drink and animal feedingstuffs.
- S20/21      When using do not eat, drink or smoke.
- S24      Avoid contact with skin.
- S37      Wear suitable gloves.
- S46      If swallowed, seek medical advice immediately and show this container or label.
- S35      This material and its container must be disposed of in a safe way.
- S57      Use appropriate container to avoid environmental contamination.
- SP 1      Do not contaminate water with the product or its container (Do not clean application equipment near surface water/Avoid contamination via drains from farmyards and roads).

**2.3. Other hazards**

This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).  
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

**SECTION 3: Composition/information on ingredients**

**3.1. Substances**

Not applicable

**3.2. Mixtures**

Classification according to Directive 67/548/EEC	Classification according to Regulation (EU) 1272/2008 (CLP)	Concentration



**AVAUNT® 150 EC**

Version 4.0 (replaces: Version 3.0)  
Revision Date 11.06.2015

Ref. 130000027381

**Indoxacarb (CAS-No.173584-44-6)**

T;R25 R48/25 Xn;R20 R43 N;R50 R53	Acute Tox. 3; H301 Acute Tox. 4; H332 Skin Sens. 1B; H317 STOT RE 1; H372 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	15,84 %
--	--	---------

**2-Ethylhexan-1-ol (CAS-No.104-76-7)**

Xi;R36/37/38 R67	Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335, H336	>= 1 - < 5 %
---------------------	--	--------------

**Calcium Petroleum Sulfonate (CAS-No.61789-86-4)**

Xi;R43	Skin Sens. 1B; H317	>= 1 - < 5 %
--------	---------------------	--------------

For the full text of the R-phrases mentioned in this Section, see Section 16.  
For the full text of the H-Statements mentioned in this Section, see Section 16.

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

- General advice : Never give anything by mouth to an unconscious person.
- Inhalation : Move to fresh air. Consult a physician after significant exposure. Artificial respiration and/or oxygen may be necessary.
- Skin contact : Take off contaminated clothing and shoes immediately. Wash off immediately with soap and plenty of water. In the case of skin irritation or allergic reactions see a physician. Wash contaminated clothing before re-use.
- Eye contact : If easy to do, remove contact lens, if worn. Hold eye open and rinse slowly and gently with water for 15-20 minutes. If eye irritation persists, consult a specialist.
- Ingestion : Call a physician or poison control centre immediately. DO NOT induce vomiting unless directed to do so by a physician or poison control center. If victim is conscious: Rinse mouth with water.

**4.2. Most important symptoms and effects, both acute and delayed**

- Symptoms : No cases of human intoxication are known and the symptoms of experimental intoxication are not known.

**4.3. Indication of any immediate medical attention and special treatment needed**

- Treatment : Treat symptomatically.



## AVAUNT® 150 EC

Version 4.0 (replaces: Version 3.0)  
Revision Date 11.06.2015

Ref. 130000027381

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray, Foam, Dry chemical, Carbon dioxide (CO<sub>2</sub>)

Extinguishing media which shall not be used for safety reasons : High volume water jet, (contamination risk)

#### 5.2. Special hazards arising from the substance or mixture

Specific hazards during firefighting : Hazardous decomposition products formed under fire conditions. Carbon dioxide (CO<sub>2</sub>) Nitrogen oxides (NO<sub>x</sub>)

#### 5.3. Advice for firefighters

Special protective equipment for firefighters : Wear full protective clothing and self-contained breathing apparatus.

Further information : Prevent fire extinguishing water from contaminating surface water or the ground water system. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

: (on small fires) If area is heavily exposed to fire and if conditions permit, let fire burn itself out since water may increase the area contaminated. Cool containers/tanks with water spray.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions : Control access to area. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Ventilate spill area. Take precautionary measures against static discharges. Avoid contact with skin, eyes and clothing. Use personal protective equipment. Refer to protective measures listed in sections 7 and 8.

#### 6.2. Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so. Use appropriate container to avoid environmental contamination. Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained. If the spill area is porous, the contaminated material must be collected for subsequent treatment or disposal. If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3. Methods and materials for containment and cleaning up

Methods for cleaning up : Clean-up methods - small spillage Soak up with inert absorbent material. Sweep up or vacuum up spillage and collect in suitable container for disposal. Clean-up methods - large spillage Contain spillage, soak up with non-



## AVAUNT® 150 EC

Version 4.0 (replaces: Version 3.0)  
Revision Date 11.06.2015

Ref. 130000027381

combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Large spills should be collected mechanically (remove by pumping) for disposal. Collect leaking liquid in sealable (metal/plastic) containers.

Other information : Never return spills in original containers for re-use. Dispose of in accordance with local regulations.

### 6.4. Reference to other sections

For personal protection see section 8., For disposal instructions see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Advice on safe handling : Use only according to our recommendations. Wear personal protective equipment. For personal protection see section 8. Use only clean equipment. Provide adequate ventilation. Do not breathe vapours or spray mist. When opening containers, avoid breathing vapours that may be emanating. Prepare the working solution as given on the label(s) and/or the user instructions. Use prepared working solution as soon as possible - Do not store. To avoid spills during handling keep bottle on a metal tray. Wash hands before breaks and immediately after handling the product. Remove and wash contaminated clothing before re-use. Never return unused material to storage receptacle. Avoid exceeding the given occupational exposure limits (see section 8).

Advice on protection against fire and explosion : Keep away from heat and sources of ignition. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded.

### 7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in a place accessible by authorized persons only. Store in original container. Keep in properly labelled containers. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs.

Advice on common storage : No special restrictions on storage with other products.

Storage temperature : > 3 - < 54 °C

Other data : Protect from freezing. Stable under recommended storage conditions.

### 7.3. Specific end use(s)

Plant protection products subject to Regulation (EC) No 1107/2009.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters



## AVAUNT® 150 EC

Version 4.0 (replaces: Version 3.0)  
Revision Date 11.06.2015

Ref. 130000027381

If sub-section is empty then no values are applicable.

### 8.2. Exposure controls

Engineering measures : Ensure adequate ventilation, especially in confined areas. Use sufficient ventilation to keep employee exposure below recommended limits.

Eye protection : Safety glasses with side-shields conforming to EN166

Hand protection : Material: Nitrile rubber  
Glove thickness: 0,4 - 0,7 mm  
Glove length: Gauntlets of 35 cm long or longer.  
Protection index: Class 6  
Wearing time: > 480 min  
The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The suitability for a specific workplace should be discussed with the producers of the protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case. The exact break through time can be obtained from the protective glove producer and this has to be observed. Gloves must be inspected prior to use. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Gauntlets of 35 cm long or longer shall be worn over the combination sleeve. Before removing gloves clean them with soap and water.

Skin and body protection : Manufacturing and processing work: Full protective clothing Type 6 (EN 13034)

Mixer and loaders must wear: Full protective clothing Type 6 (EN 13034)  
Rubber apron Rubber or plastic boots

Spray application - outdoor: Tractor / sprayer with hood: No personal body protection normally required.

Tractor / sprayer without hood: Full protective clothing Type 4 (EN 14605)  
Rubber or plastic boots

Backpack / knapsack sprayer: Full protective clothing Type 4 (EN 14605)  
Rubber or plastic boots

Mechanical automatized spray application in closed tunnel: No personal body protection normally required.

When exceptional circumstances require an access to the treated area before the end of re-entry periods, wear full protective clothing Type 6 (EN 13034), nitrile rubber gloves class 3 (EN 374) and nitrile rubber boots (EN 13832-3 / EN ISO 20345).

To optimize the ergonomoy it may be recommended to use cotton underwear when wearing some fabrics. Take advice from supplier.



## AVAUNT® 150 EC

Version 4.0 (replaces: Version 3.0)  
Revision Date 11.06.2015

Ref. 130000027381

Garment materials that are resistant to both water vapour and air will maximise wearing comfort. Materials should be robust to maintain the integrity and barrier in use.

The permeation resistance of the fabric must be verified independently of the « type » protection recommended, to ensure an appropriate performance level of the material adequate to the corresponding agent and type of exposure.

- Protective measures** : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. All chemical protective clothing should be visually inspected prior to use. Clothing and gloves should be replaced in case of chemical or physical damage or if contaminated. Only protected handlers may be in the area during application.
- Hygiene measures** : Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing. Keep working clothes separately. Contaminated work clothing should not be allowed out of the workplace. Wash hands and face before breaks and immediately after handling the product. When using do not eat, drink or smoke. Keep away from food, drink and animal feedingstuffs. Remove clothing/PPE immediately if material gets inside. For environmental protection remove and wash all contaminated protective equipment before re-use. Dispose of rinse water in accordance with local and national regulations.
- Respiratory protection** : Manufacturing and processing work: Half mask with vapour filter A1 (EN 141)
- Mixer and loaders must wear: Half mask with vapour filter A1 (EN 141)
- Spray application - outdoor: Tractor / sprayer with hood: No personal respiratory protective equipment normally required.
- Tractor / sprayer without hood: Low application: Half mask with a particle filter P1 (EN 143). Middle-height application: Half mask with a particle filter P2 (EN 143)
- High application: Half mask with a particle filter P2 (EN 143)
- Backpack / knapsack sprayer: Low application: Half mask with a particle filter P1 (EN 143). Middle-height application: Half mask with a particle filter P2 (EN 143)
- High application: Half mask with a particle filter P2 (EN 143)
- Mechanical automatized spray application in closed tunnel: No personal respiratory protective equipment normally required.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

- Form : liquid
- Colour : amber



**AVAUNT® 150 EC**

Version 4.0 (replaces: Version 3.0)  
Revision Date 11.06.2015

Ref. 130000027381

Odour	: of burnt sugar
Odour Threshold	: not determined
pH	: 5,4 at 10 g/l ( 25 °C)
Melting point/range	: Not applicable
Boiling point/boiling range	: Not available for this mixture.
Flash point	: 69 °C
Flammability (solid, gas)	: The product is not flammable.
Thermal decomposition	: Not available for this mixture.
Auto-ignition temperature	: 255 °C , Test Type :Auto-ignition temperature
Oxidizing properties	: The product is not oxidizing.
Explosive properties	: Not explosive
Lower explosion limit/ lower flammability limit	: Not available for this mixture.
Upper explosion limit/ upper flammability limit	: Not available for this mixture.
Vapour pressure	: Not available for this mixture.
Relative density	: 0,9494 at 20 °C
Water solubility	: emulsifiable
Partition coefficient: n-octanol/water	: Not applicable
Viscosity, dynamic	: 5,6 mPa.s at 25 °C
Viscosity, kinematic	: 4,68 mm <sup>2</sup> /s at 20 °C
Relative vapour density	: Not available for this mixture.
Evaporation rate	: Not available for this mixture.

**9.2. Other information**

Phys.-chem./other information : No other data to be specially mentioned.

**SECTION 10: Stability and reactivity**

**10.1. Reactivity** : No hazards to be specially mentioned.

**10.2. Chemical stability** : The product is chemically stable under recommended conditions of storage, use





## AVAUNT® 150 EC

Version 4.0 (replaces: Version 3.0)  
Revision Date 11.06.2015

Ref. 130000027381

and temperature.

- 10.3. Possibility of hazardous reactions** : No dangerous reaction known under conditions of normal use. Polymerization will not occur. No decomposition if stored and applied as directed.
- 10.4. Conditions to avoid** : Temperature : > 54 °C Protect from frost.
- 10.5. Incompatible materials** : No materials to be especially mentioned.
- 10.6. Hazardous decomposition products** : No materials to be especially mentioned.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Acute oral toxicity

LD50 / Rat : 976,8 mg/kg  
Method: OECD Test Guideline 425  
(Data on the product itself) Information source: Internal study report

##### Acute inhalation toxicity

LC50 / 4 h Rat : > 5,2 mg/l  
Method: OECD Test Guideline 403  
(Data on the product itself) Information source: Internal study report

##### Acute dermal toxicity

LD50 / Rat : > 5 mg/kg  
Method: OECD Test Guideline 402  
(Data on the product itself) Information source: Internal study report

##### Skin irritation

Rabbit  
Result: Irritating to skin.  
Method: OECD Test Guideline 404  
(Data on the product itself) Information source: Internal study report

##### Eye irritation

Rabbit  
Result: No eye irritation  
Method: OECD Test Guideline 405  
(Data on the product itself) Information source: Internal study report

##### Sensitisation

Guinea pig Maximisation Test (GPMT)  
Result: Animal test did not cause sensitization by skin contact.  
Method: OECD Test Guideline 406  
(Data on the product itself) Information source: Internal study report



## AVAUNT® 150 EC

Version 4.0 (replaces: Version 3.0)  
Revision Date 11.06.2015

Ref. 130000027381

### Repeated dose toxicity

Oral - feed Rat  
Exposure time: 28 d  
Method: OECD Test Guideline 408  
Information source: Internal study report

Oral - feed Rat  
Exposure time: 90 d  
Method: OECD Test Guideline 408  
Information source: Internal study report

## SECTION 12: Ecological information

### 12.1. Toxicity

#### Toxicity to fish

static test / LC50 / 96 h / *Oncorhynchus mykiss* (rainbow trout): 7,0 mg/l  
Method: OECD Test Guideline 203  
(Data on the product itself) Information source: Internal study report

#### Toxicity to aquatic plants

static test / ErC50 / 72 h / *Pseudokirchneriella subcapitata* (green algae): > 16 mg/l  
Method: OECD Test Guideline 201  
(Data on the product itself) Information source: Internal study report

#### Toxicity to aquatic invertebrates

static test / EC50 / 48 h / *Daphnia magna* (Water flea): 1,67 mg/l  
Method: OECD Test Guideline 202  
(Data on the product itself) Information source: Internal study report

#### Chronic toxicity to fish

- Indoxacarb  
Early Life-Stage / NOEC / 90 d / *Oncorhynchus mykiss* (rainbow trout): 0,15 mg/l

#### Chronic toxicity to aquatic Invertebrates

- Indoxacarb  
NOEC / 21 d / *Daphnia magna* (Water flea): 0,9 mg/l

### 12.2. Persistence and degradability

#### Biodegradability

Not readily biodegradable. Estimation based on data obtained on active ingredient.

### 12.3. Bioaccumulative potential

#### Bioaccumulation



## AVAUNT® 150 EC

Version 4.0 (replaces: Version 3.0)  
Revision Date 11.06.2015

Ref. 130000027381

Does not bioaccumulate. Estimation based on data obtained on active ingredient.

### 12.4. Mobility in soil

Mobility in soil

Under actual use conditions the product has a low potential of mobility in soil.

### 12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT). / This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

### 12.6. Other adverse effects

#### Additional ecological information

No other ecological effects to be specially mentioned

See product label for additional application instructions relating to environmental precautions.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product : In accordance with local and national regulations. Must be incinerated in a suitable incineration plant holding a permit delivered by the competent authorities. Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Do not re-use empty containers.

European Waste Catalogue number : 020108: agrochemical waste containing dangerous substances

## SECTION 14: Transport information

### ADR

14.1. UN number: 3082  
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Indoxacarb)  
14.3. Transport hazard class(es): 9  
14.4. Packing group: III  
14.5. Environmental hazards: Environmentally hazardous  
14.6. Special precautions for user:  
Tunnel restriction code: (E)

### IATA\_C

14.1. UN number: 3082  
14.2. UN proper shipping name: Environmentally hazardous substance, liquid, n.o.s. (Indoxacarb)  
14.3. Transport hazard class(es): 9  
14.4. Packing group: III  
14.5. Environmental hazards : For further information see Section 12.



## AVAUNT® 150 EC

Version 4.0 (replaces: Version 3.0)  
Revision Date 11.06.2015

Ref. 130000027381

- 14.6. Special precautions for user:  
DuPont internal recommendations and transport guidance: ICAO / IATA cargo aircraft only

### IMDG

- 14.1. UN number: 3082  
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S. (Indoxacarb)  
14.3. Transport hazard class(es): 9  
14.4. Packing group: III  
14.5. Environmental hazards : Marine pollutant  
14.6. Special precautions for user:  
no data available

- 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code  
Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations : The mixture is classified as dangerous in accordance with Directive 1999/45/EC. Take note of Dir 94/33/EC on the protection of young people at work. Take note of Dir 92/85/EEC on the safety and health at work of pregnant workers. Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work. Take note of Directive 96/82/EC on the control of major-accident hazards involving dangerous substances. Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values.

## SECTION 16: Other information Text of R-phrases mentioned in Section 3

R20 Harmful by inhalation.  
R22 Harmful if swallowed.  
R25 Toxic if swallowed.  
R36/37/38 Irritating to eyes, respiratory system and skin.  
R38 Irritating to skin.  
R43 May cause sensitisation by skin contact.  
R48/22 Harmful: danger of serious damage to health by prolonged exposure if swallowed.  
R48/25 Toxic: danger of serious damage to health by prolonged exposure if swallowed.  
R50 Very toxic to aquatic organisms.

### Full text of H-Statements referred to under section 3.

H301 Toxic if swallowed.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H372 Causes damage to organs through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
Other information professional use



## AVAUNT® 150 EC

Version 4.0 (replaces: Version 3.0)  
Revision Date 11.06.2015

Ref. 130000027381

### Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute toxicity estimate
CAS-No.	Chemical Abstracts Service number
CLP	Classification, Labelling and Packaging
EbC50	Concentration at which 50% reduction of biomass is observed
EC50	Median effective concentration
EN	European Norm
EPA	Environmental Protection Agency
ErC50	Concentration at which a 50% inhibition of growth rate is observed
EyC50	Concentration at which 50 % inhibition of yield is observed
IATA_C	International Air Transport Association (Cargo)
IBC	International Bulk Chemical Code
ICAO	International Civil Aviation Organization
ISO	International Standard Organization
IMDG	International Maritime Dangerous Goods
LC50	Median Lethal Concentration
LD50	Median Lethal Dose
LOEC	Lowest Observed Effect Concentration
LOEL	Lowest observed effect level
MARPOL	International Convention for the Prevention of Marine Pollution from Ships
n.o.s.	Not Otherwise Specified
NOAEC	No Observed Adverse Effect Concentration
NOAEL	No observed adverse effect level
NOEC	No Observed Effect Concentration
NOEL	No Observed Effect Level
OECD	Organisation for Economic Co-operation and Development
OPPTS	Office of Prevention, Pesticides and Toxic Substances
PBT	Persistent, Bioaccumulative and Toxic
STEL	Short term exposure limit
TWA	Time Weighted Average (TWA):
vPvB	very Persistent and very Bioaccumulative

### Further information

(R) Registered trademark of E.I. du Pont de Nemours and Company  
Before use read DuPont's safety information., Take notice of the directions of use on the label.

Significant change from previous version is denoted with a double bar.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The above information relates only to the specific material(s) designated herein and may not be valid for such material(s) used in combination with any other materials or in any process or if the material is altered or processed, unless specified in the text.